

# **SAFETY DATA SHEET**

# LITHIUM NANOPARTICLES FLOW FROM 1NM TO 100NM

MANUFACTURER/SUPPLIER	DESCRIPTION	
JAVI NANOTECHNOLOGY CORP EIN 84-2905354  8095 NW 90™ Street, Medley, Florida 33166.	Technology of Lithium Nanoparticle	s Flow CAS# 7439-93-2
	PACKING	
	Glass bottles containing 1000 (thousand) grams	
	FORMULA	PURITY
	Li	99,9998%
	CHEMICAL PROPERTIES	
	Appearance	Fluid
	Molecular Weight	9.961
	Melting/Boiling Point	180°
	Odor	Odorless
	рН	No data available
	Initial Boiling Point and Boiling Range	1342°
	Water Solubility	0.535 g/cm <sup>3</sup>

HAZARD IDENTIFICATION		
DESCRIPTION	Xn Harmful F Highly flammable Information pertaining to particular dangers for man and environment: R 11 Highly flammable R 62 possible risk of impaired fertility R 63 Possible risk of harm to the unborn child	
CLASSIFICATION SYSTEM	HMIS ratings (scale 0-4)  (Hazardous Materials Identification System)  Health (acute effects) = 1 Flammability = 3 Reactivity = 1	











# **SAFETY DATA SHEET**

# LITHIUM NANOPARTICLES FLOW FROM 1NM TO 100NM

FIRST AID MEASURES		
AFTER INHALATION	Supply fresh air, if required, provide artificial respiration. Keep patient warm. Seek immediate medical advice	
AFTER SKIN CONTACT	Immediately wash with water and soap and rinse thoroughly Seek immediate medical advice	
AFTER EYE CONTACT	Rinse opened eye for several minutes under running water then consult doctor	
AFTER SWALLOWING	Seek immediate medical advice	

FIRE FIGHTING MEASURES	ACCIDENTAL RELEASE MEASURES
Suitable extinguishing agents:	Person related safety precautions:
Special powder for metal fires Do not use water	Wear protective equipment Keep unprotected persons away
	Ensure adequate ventilation
For safety reasons unsuitable extinguishing agents:	Keep away from ignition sources
Water	Measures for environmental protection:
Protective equipment	Do not allow material to be released to the
Wear self-contained respirator Wear fully protective impervious suit	environment without proper governmental permits
	Measures for cleaning/collecting:
	Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents Keep away from ignition sources

# **HANDLING AND STORAGE**

Information for safe handling. Keep the container tightly sealed. Store in cool, dry places in tightly closed containers. Ensure good ventilation at the workplace

## Information about protection against explosions and fires:

Keep ignition sources away. Protect against electrostatic charges Fumes can combine with air to form an explosive mixture

# Storage

Store in a cool location











## SAFETY DATA SHEET

### LITHIUM NANOPARTICLES FLOW FROM 1NM TO 100NM

### PERSONAL PROTECTION

#### **TOXICOLOGICAL INFORMATION**

## **GENERAL PROTECTIVE AND HYGIENIC MEASURES**

The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Remove all soiled and contaminated clothing immediately. Wash hands before breaks and at the end of work. Avoid contact with eyes and skin

Breathing equipment: Use suitable respirator when

high concentrations are present

Protection of hands: Impervious gloves

Eve protection: Safety glasses

Body protection: Protective work clothing

### **ACUTE TOXICITY**

Primary irritant effect

On the skin: Irritant to skin and mucous membranes

On the eye: Irritating effect

Sensitization: No sensitizing effects known

Subacute to chronic toxicity: Lithium compounds may be irritating to the skin, eyes and respiratory tract. They may cause metal fume fever, hemolysis of the red blood cells and injury to the liver, lungs, kidneys and pancreas. Ingestion may also cause vomiting, gastric pain, dizziness, anemia, cramps, convulsions, shock, coma and death. Lithium solutions may cause

sensitization reactions

# STABILITY AND REACTIVITY

Conditions to be avoided/thermal decomposition: Decomposition will not occur if used and stored according to specifications. Dangerous reactions. Contact with acids releases flammable gases. Dangerous products of decomposition. Toxic metal oxide fume

#### TRANSPORT INFORMATION

#### **DOT REGULATIONS**

Hazard class: 4.3

**Identification number: UN1415** 

Packing group: II

**Proper shipping name:** Metal powders, flammable,

N.O.S. (lithium)

# LAND TRANSPORT ADR/RID (cross-border)

ADR/RID class: 4.3 Flammable solids

**Item:** 13c

Danger code (Kemmler): 40

UN-Number: 1415

**Description of goods:** Metal powders, flammable,

N.O.S. (lithium)

#### MARITIME TRANSPORT IMDG

IMDG Class: 4.3 **UN Number:** 1415 Packing group: II

Proper shipping name: Metal powders, flammable,

N.O.S. (lithium)

### AIR TRANSPORT ICAO-TI AND IATA-DGR

ICAO/IATA Class: 4.3 UN/ID Number: 1415 Packing group: ||

**Proper shipping name:** Metal powders, flammable,

N.O.S. (lithium)







